

CLEANTECH ELF-C



CleanTech ELF-C Features

Ideal for public use, cruise lines, daycare, food service, and any environment that would benefit from increased hand hygiene compliance.

- Streamlined stainless look design fits any cabinetry
- Designed for public use
- Stainless cabinet option available
- Low profile aesthetics
- Custom cabinets available

Dimensions

17 1/4" width x 15 3/4" depth x 22 1/2" height

Weight

34 lbs. (varies with options)

Shipping Weight

49 lbs. (varies with options)

Cycle and Activation

Automatic, via infrared photo-optical sensor
12-second wash and rinse cycle

Handwash Compliance Monitor

Counts number of handwash cycles
Optional automatic reset of counter

Water Consumption

0.6 gallons per hand wash cycle

Electrical

100-250 VAC, 50/60 Hz, 300 W

Plumbing

2 each, 3/4" male hose, hot and cold minimum 4 GPM,
40-80 PSI, 60 PSI optimum

Drain

Standard 1 1/5" drain stub
P-Trap to be supplied by facility
Ideal drain height 18-22" from floor

Solutions Storage

1 - One gallon or optional 10-liter container of Hand Soap

Solutions

Required solutions provided by Meritech
(Other solutions will void warranty)

Protective Modes

Current limited motor
Overheat auto shut off

Options

Daily auto-reset counter
Stainless cabinet (single or double)
Dual machine stainless cabinet
Single machine stainless cabinet



meritech.com • 800.932.7707

CleanTech Automated Handwashing and Bootwashing Systems are protected by the following U.S. Patents: U.S. Patent #5,265,628; #5,823,447; #7,607,442; #7,607,443; #7,617,830; #7,641,740; #7,659,824; #7,682,464; #7,698,770; #7,754,021; #7,754,022; #7,757,700; #7,758,701; other patents pending.